



BC Pump Model appx. 2900 rpm.	Threephase Motor kW	Flanges		Dimensions of pump													Net weight ~ lbs.
		DN <sub>S</sub>	DN <sub>D</sub>	A	C	F	G	H	R	g	h	m	n	ø <sub>s</sub>	t		
BC 25-071/0132	0.4	G 1 1/4	G 1	2.047	5.708	12.63	4.88	4.17	8.189	1.968	1.496	6.3	4.72	.354	4.9213	19.84	
BC 25-071/0157	0.65	G 1 1/4	G 1	2.047	5.708	12.63	4.88	4.17	8.189	1.968	1.496	6.3	4.72	.354	4.9213	22.05	
BC 25-091/0157	0.85	G 1 1/4	G 1	2.047	5.708	12.63	4.88	4.17	8.189	1.968	1.496	6.3	4.72	.354	4.9213	26.46	
BC 25-121/0132	0.65	G 1 1/4	G 1	2.047	5.708	12.63	4.88	4.17	8.189	1.968	1.496	6.3	4.72	.354	4.9213	22.05	
BC 25-121/0157	1.1	G 1 1/4	G 1	2.047	5.708	13.11	4.88	4.17	8.189	1.968	1.496	6.3	4.72	.354	4.9213	26.46	
BC 25-121/0176	1.5	G 1 1/4	G 1	2.047	5.787	14.17	5.197	4.64	9.134	2.165	1.574	7.08	5.51	.354	4.9213	33.07	
BC 25-072/0132	0.9	G 1 1/4	G 1	3.425	7.086	13.98	4.88	4.17	8.189	1.968	1.496	6.3	4.72	.354	4.9213	26.46	
BC 25-072/1153	1.1	G 1 1/4	G 1	3.425	7.086	14.45	4.88	4.17	8.189	1.968	1.496	6.3	4.72	.354	4.9213	28.66	
BC 25-072/0153	1.35	G 1 1/4	G 1	3.425	7.165	15.04	5.197	4.64	9.134	2.165	1.574	7.08	5.51	.354	4.9213	33.07	
BC 25-072/1176	1.7	G 1 1/4	G 1	3.425	7.165	15.59	5.197	4.64	9.134	2.165	1.574	7.08	5.51	.354	4.9213	39.68	
BC 25-122/0132	1.35	G 1 1/4	G 1	3.425	7.165	15.08	4.88	4.17	8.189	2.165	1.574	7.08	5.51	.354	4.9213	30.86	
BC 25-122/1157	1.75	G 1 1/4	G 1	3.425	7.165	15.59	4.88	4.17	8.189	2.165	1.574	7.08	5.51	.354	4.9213	35.27	
BC 25-122/0157	2.25	G 1 1/4	G 1	3.425	7.716	15.63	5.197	4.64	9.134	2.559	1.574	7.08	5.51	.354	4.9213	52.91	
BC 25-122/1176	2.7	G 1 1/4	G 1	3.425	7.716	18.11	5.197	4.64	9.134	2.559	1.574	7.08	5.51	.354	4.9213	57.32	

Inches

BC

Stainless Steel  
In-Line Centrifugal Pump

Motor: 60Hz  
Attention: actual motor dimensions possible may differ from the drawing.  
Subject to alteration! ANSI Companion flanges available upon request

Shanley Pump  
& Equipment, Inc.

