



E Screwed Plug G 1/8

Flanges	øD	øk	ød	Number of holes
DN 32	5.5118	3.937	0.7087	4
DN 40	5.9055	4.3307	0.7087	4
DN 50	6.4961	4.9213	0.7087	4
DN 65	7.2835	5.7087	0.7087	4
DN 80	7.874	6.2992	0.7087	8

CB Pump Model appx. 2900 rpm.	Threephase Motor				Flanges		Dimensions of pump							Pump with footing					Net weight ≈ lbs.
	265V	230V	≈ L	≈ M	DN _S	DN _D	A	B	C	G	H	R	X	g	m	n	t	u	
	460V	400V																	
CB 32-160/151	3.0	3.0	12.95	4.88	1.97	1.26	3.15	5.59	2.76	7.09	6.29	11.65	4.33	4.69	9.45	7.48	0.79	7.91	77.16
CB 32-160/166	4.0	4.0	13.86	5.55	1.97	1.26	3.15	5.59	2.76	7.09	6.29	11.65	4.33	4.69	9.45	7.48	0.79	7.91	93.7
CB 40-125/125	3.0	3.0	13.03	4.88	2.56	1.58	3.15	5.51	2.76	6.29	5.19	10	4.53	4.65	9.45	7.48	0.75	7.91	66.14
CB 40-125/140	4.0	4.0	13.94	5.55	2.56	1.58	3.15	5.51	2.76	6.29	5.19	10	4.53	4.65	9.45	7.48	0.75	7.91	83.78

Inches

CB

Stainless Steel Centrifugal Pump

Motor: 60Hz

Attention: actual motor dimensions possible may differ from the drawing.

Subject to alteration! ANSI Companion flanges available upon request

Shanley Pump
& Equipment, Inc.

